

VIMEK 610 SE BIOCOMBI

VIMEK[®]



New powerful Common Rail engine

at 68 Hp Stage 3B/4 Final

Hydraulic compressing poles

can compress the load up to 30%

New powerful hydrostatic

Drive modes "Forest", "Road" and "ECO"

Vimek felling grapple saw cuts up to 30 cm

in combination with Vimek brake link

Crane with extension arm as option

Crane reach total 6,50 m

VIMEK 610 SE BIOCOMBI

TECHNICAL SPECIFICATION

Motor

CAT C2,2T CRDI 50 kW

Transmission

Hydrostatic / mechanical

Front tires

500/60-22,5 or 405/70-24

Rear tires

400/60-15,5

Ground clearness

40 cm

Hydraulic

Flow 85 l/min 175 bar

Length

Standard 6,90 m (load length 3,30 m, loading area 1,85 m²)

Long 7,60 m (load length 4,00 m, loading area 1,65 m²)

Width

1,90 m or 2,00 m

Loading capacity

5,000 kg

Weight incl. crane

4,900 Kg

Crane

Vimek - Mowi P25

– Max reach, 5,20 m

– Lifting capacity at 5,20 m, 400 kg

Felling grapple saw

Including accumulation arms

– Max cutting diameter 300 mm

– Weight 195 kg

EQUIPMENT

Standard

Air condition

Half LED lights including roof frame

Radio with Bluetooth

Options

Tilt grapple 0,16 m²

Crane damping system

Pneumatic chair

Refueling pump for hydraulic oil

Refueling pump for diesel

Radio controlled hydraulic winch

Sun blinds

Diesel engine heating system

Callstart for diesel engine

Full LED lights including roof frame

Sprinkler system

Grease system for saw chain

Tow hitch

PC with rear camera

Rear camera

Extra accessories

Wheel tracks

Wheel chains 500/60-22,5 or 405/70-24

Bucket attachment

Dolly trailer

Chain saw holder

VIMEK®

*The machine on the picture can be extra equipped.

© 2013 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, their respective logos, Caterpillar Yellow, the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and Aug. not be used without permission.

Version 1, June 2017

For more information and to find your nearest retailer, please visit our website
www.vimek.com