


VIMEK 630 MINIMASTER

VIMEK®



Frame steering as standard

For unique manoeuvre and traction

8-wheel driven mini-forwarder

Servo steering and unique terrain characteristics

Ground clearance of 38 cm

Wide range of options

and extra accessories for different needs

VIMEK 630 MINIMASTER

TECHNICAL SPECIFICATION

Engine

Honda 630 cc

Fuel tank

14 liters

Gear box

High, low, reverse

Transmission

Variable mechanical

Speed

0–25 km/hour

Tires

27 x 11 x 14

Weight tractor

524 Kg

Weight incl. crane and trailer

1200 Kg

Ground clearness

38 cm

Length

2,15 m

Width

1,30 m

Height

2,35 m with Rollbar

Servo steering

Hydraulic Orbitrol

Rear axle

Oscillation +/- 30°

Hydraulic

20 l/min 175 bar

Multi levers or 2-level joysticks

Crane

Vimek 362

– Max reach, 3,60 m

– Turning angle, 210°

– Gripping area, 0,12 m²

Driven trailer with frame steering

Bogie oscillation, 25 cm

Loading capacity, 2000 Kg

Loading area, 0,80 m²

EQUIPMENT

Options

Frame for hydraulic valves and lights

LED lights forward and backwards

Crane damping system

Frame steering

Radio controlled hydraulic winch

Extra accessories

Bogie tracks

Snow blade

Bucket attachments

Tow hitch 50 mm

Combi tank for gas/oil

Chain saw holder