

Dual control

with market's sharpest swing angle

DASA Forester bucking system H50 or H70

enables transportation on a dolly trailer



Equipment

Air conditioning

Medium LED lightning

Radio with Bluetooth

Pneumatic chair

Sprinkler system

Filling pump hydraulic oil

Refueling pump diesel

Diesel engine heater

Callstarter diesel engine heater

Crane damping system

Sun blinds

Large LED lightning

Stump treatment system

PC

Rear camera

Color marking

Clamshell bucket

Wheel chains 500/60-22.5 or 405/70-24

Computer caliper

Vimek C12 clearing head

Chainsaw holder

Dolly trailer



See **technical specifications** for Vimek C12 clearing head on page 11.





Technical specifications

Engine

CAT C2.2T CRDI 55 kW

Swing angle

80

Transmission

Hydrostatic / mechanical

Tyres

500/60-22.5 or 405/70-24

<u>Hydraulic</u>

135 L/min

Ground clearance

40 cm

Wheelbase

2.10 m

Length

4.6 m

Width

1.80 m or 2.05 m

Weight

From 4,500 kg

Crane

Vimek - Mowi 2046

Range: 4.60 m

Harvesting unit

Keto Forst Supreme V4

Weight: 296 kg

Max. diameter: 300 mm

10 cc saw engine

Nisula 325H (option)

Weight: 285 kg

Max. diameter: 340 mm

10 cc saw engine

Bucking system

DASA H50/H70



The machines displayed may be extra equipped.
© 2022 Vimek AB. All rights reserved.

Version 1, Mars 2022

www.vimek.com

