404 T8 DUO

Vimek 404 T8 DUO unites the best of both worlds. It combines a harvester and a forwarder in one machine.



Powerful and fuel efficient CAT engine

Dual control

with market's sharpest swing angle

DASA Forester bucking system
H50 or H70

Keto Forst Keto V4

Improved harvesting head

Powerful hydrostatic with different drive modes

Disconnectable wheel drive enables transportation on a dolly trailer



## **Equipment**

Air conditioning

**Medium LED lightning** 

Radio with Bluetooth

Pneumatic chair

Sprinkler system

Filling pump hydraulic oil

Refueling pump diesel

Diesel engine heater

Callstarter diesel engine heater

Crane damping system

Sun blinds

Large LED lightning

Stump treatment system

PC

Rear camera

**Tool holder** 

**Color marking** 

Clamshell bucket

Boogie tracks, trailer

Wheel chains 500/60-22.5 or 405/70-24

Computer caliper

Vimek C12 clearing head

Transport and tool replacement kit

Chainsaw holder

**Dolly trailer** 



See **technical specifications** for Vimek C12 clearing head on page 11.



## 404 T8 DUO

## **Technical specifications**

**Engine** 

CAT C2.2T CRDI 55 kW

Swing angle

80

Transmission

Hydrostatic / mechanical

Tyres

405/70-24 or 500/60-22.5

Hydraulic 135 L/min

Ground clearance

40 cm

Wheelbase

2.10 m

Length

4 65 m

9.25 m including trailer

Width

1.80 m or 2.05 m

Weight

From 4,700 kg, trailer excluded

Loading area

Loading area 3.40 m with cargo space 2.00 m<sup>2</sup>

Loading capacity

5,500 kg

Crane

Vimek - Mowi P25

Range: 5.2 m

Lifting capacity: 400 kg at 5.2 m

Gripping area: 0.16 m<sup>2</sup>

Harvesting unit

Keto Forst Supreme V4

Weight: 296 kg

Max. diameter: 300 mm

10 cc saw engine

Nisula 325H (option)

Weight: 285 kg

Max. diameter: 340 mm

10 cc saw engine

Bucking system

**DASA H50/H70** 



The machines displayed may be extra equipped. © 2022 Vimek AB. All rights reserved.

Version 1, Mars 2022

www.vimek.com

