

Powerful and fuel efficient **CAT** engine

Powerful hydrostatic Drive modes "Forest", "Road" and "ECO"

Load sensing hydraulic system and improved crane driving characteristics

Disconnectable wheel drive enables transportation on a dolly trailer

> Active brake link with adapted braking force



Equipment

Air conditioning

Medium LED lightning

Radio with Bluetooth

Pneumatic chair

Sprinkler system

Filling pump hydraulic oil

Refueling pump diesel

Diesel engine heater

Callstarter diesel engine heater

Crane damping system

Sun blinds

Large LED lightning

PC

Rear camera

Crane with extension

Tiltable grapple 0.16 m² with Vimek

Hydraulic radio controlled winch

Chainsaw holder

Hydraulic poles

Roll-fed harvester head

Energy wood head

Boogie tracks, trailer

Wheel chains 500/60-22.5 or

405/70-24

Bucket attachment

Chainsaw holder

Dolly trailer





All Vimek forwarders (in Sweden) are registered as heavy off-road vehicles, which means that they are allowed on public roads.

610.4

Technical specifications

Engine

CAT C2.2T CRDI 55 kW

<u>Transmission</u>

Hydrostatic / mechanical

Tyres

Front: 500/60-22.5 or 405/70-24

Rear: 400/60-15.5

<u>Hydraulic</u>

120 L/min 175 bar

Ground clearance

40 cm

Length

Standard: 6.90 m

Long: 7.60 m

Width
1.90 m or 2 m

Weight

From 4,900 kg

Loading area

Loading area 3.3 m

with cargo space 1.85 m²

Loading area 4.0 m with cargo space 1.65 m²

Loading capacity

5,000 kg

Crane

Vimek - Mowi P25

Range: 5.2 m

Lifting capacity: 400 kg at 5.2 m

Vimek - Mowi P25T (option)

Range: 6.55 m

Lifting capacity: 400 kg at 5.2 m

Gripping area: 0.16 m²





The machines displayed may be extra equipped. © 2022 Vimek AB. All rights reserved.

Version 1, Mars 2022

www.vimek.com

